



浙江芯芯电子有限公司
ZHEJIANG XINXIN ELECTRICAL CO., LTD.

产品规格书

Specification of Products

产品名称：平板型

产品型号：600A

浙江芯芯电子有限公司

ZHEJIANG XINXIN ELECTRICAL CO., LTD.

地址：浙江省缙云县壶镇镇浙江丽缙五金科技产业园苍山区块内

电话：13857067071

邮编：321404

E-mail: 247145749@qq.com


<http://www.zjxxdz1.com>

拟制	审核	核准
丁国盛	李园利	麻伟阳

版本号：04 更新日期：2022.6.28

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T _J (C)	VALUE			UNIT
				Min	Type	Max	
I _{F(AV)}	Mean forward current	180 half sinewave 50Hz Double side cooled, T _S =55C	150			1476	A
I _{F(AV)}	Mean forward current	180 half sinewave 50Hz Double side cooled, T _S =90C	150			1078	A
V _{RRM}	Repetitive peak reverse voltage	V _{RRM} tp=10ms V _{RSM} = V _{RRM} +100V	150	200		1000	V
I _{RRM}	Repetitive peak current	at V _{RRM}	150			40	mA
I _{FSM}	Surge forward current	10ms half sine wave	150			19.2	KA
I ² T I	² T for fusing coordination	V _R =0.6V _{RRM}				1841	A ² s*10 ⁻³
V _{FO}	Threshold voltage		150			0.97	V
r _F	Forward slop resistance					0.27	mΩ
V _{FM}	Peak onstate voltage I	T _M =2870A, F=15KN	150			1.74	V
I _{rm}	Reverse recovery current	I _{TM} =1000A, tp= 1000 s, di/dt=-40A/s, V _R =50V	150			82.9	A
t _{rr}	Reverse recovery time					4.0	s
Q _{rr}	Recovery charge					165	C
R _{th(j-h)}	Thermal resistance Junction to heatsink	At 180° sine double side cooled Clamping force 15KN				0.033	C/W
F _m	Mounting force			10		20	KN
T _{stg}	Stored temperature			-40		160	C
W _t	Weight				260		g
Outline	ZT33cT						

Outline






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6