



浙江芯芯电子有限公司
ZHEJIANG XINXIN ELECTIRICAL CO., LTD.

产品规格书

Specification of Products

产品名称：桥式整流器

产品型号：KBPC35A

浙江芯芯电子有限公司

ZHEJIANG XINXIN ELECTIRICAL CO., LTD.

地址：浙江省缙云县壶镇镇浙江丽缙五金科技产业园苍山区块内

电话：13857067071


邮编：321404

E-mail:247145749@qq.com

<http://www.zjxxdz1.com>

拟制	审核	核准
丁国盛	李园利	麻伟阳

版本号：04 更新日期：2022.6.28



Nominal current 35 A

Alternating input voltage 70-1000 V

Dimensions 31 x 31 x 10 [mm]

Weight approx. 24 g

Standard packaging bulk

Maximum ratings

Grenzwerte

Type	Alternating input volt. V_{VRMS} [V]	Rep. peak reverse voltage V_{RRM} [V]
KBPC3501	70	100
KBPC3502	140	200
KBPC3504	280	400
KBPC3506	420	600
KBPC3508	560	800
KBPC3510	700	1000
KBPC3512	800	1200
KBPC3514	900	1400
KBPC3514	1000	1600

Repetitive peak forward current $f > 15 \text{ Hz}$ I_{FRM} 105 A

Peak forward surge current, 50Hz half sine-wave $T_A = 25^\circ \text{C}$ I_{FRM} 350 A

Rating for fusing, $t < 10 \text{ ms}$ $T_A = 25^\circ \text{C}$ $I^2 t$ 613 A²s

Operating junction temperature T_j -40...+150°C

Storage temperature T_s -40...+150°C

Silicon-Bridge Rectifiers

KBPC 35A

Characteristics

Kennwerte

Max. current with cooling fin 300 cm ²	$T_A=50^{\circ}\text{C}$	R-load	I _{FAV}	35.0 A
Forward voltage	$T_j=25^{\circ}\text{C}$	$I_{FM}=18\text{A}$	V _{FM}	< 1.2 V
Leakage current	$T_j=25^{\circ}\text{C}$	$V_R=V_{RRM}$	I _R	< 10 μA
Isolation voltage terminals to case			V _{ISO}	>2500 V
Thermal resistance junction to case			R _{thC}	< 2.0 K/W
Admissible torque for mounting		M 5		2 ± 10 % Nm

