



浙江芯芯电子有限公司
ZHEJIANG XINXIN ELECTIRICAL CO., LTD.

产品规格书

Specification of Products

产品名称：整流单管模块

产品型号：MD250A

浙江芯芯电子有限公司

ZHEJIANG XINXIN ELECTIRICAL CO., LTD.

地址：浙江省缙云县壶镇镇浙江丽缙五金科技产业园苍山区块内

电话：13857067071

邮编：321404

E-mail: 247145749@qq.com

<http://www.zjxxdz1.com>


拟制	审核	核准
丁国盛	李园利	麻伟阳

版本号：04 更新日期：2022.6.28







SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T _j (°C)	VALUE			UNIT
				Min	Type	Max	
I _{F(AV)}	Mean forward current	180° half sinewave 50Hz Single side cooled, $\bar{T}=100^{\circ}\text{C}$	150			250	A
I _{F (RMS)}	RMS forward current	Single side cooled, $\bar{T}=100^{\circ}\text{C}$	150			393	A
V _{RRM}	Repetitive peak reverse voltage	V _{RRM} tp=10ms V _{RSM} = V _{DRM} &V _{RRM} +200V	150	600		1800	V
I _{RRM}	Repetitive peak current	at V _{RRM}	150			20	mA
I _{FSM}	Surge forward current	10ms half sinewave	150			12.5	KA
I ² _t I	² T for fusing coordination	V _R =0.6V _{RRM}				797	A ² s*10 ³
V _{FO}	Threshold voltage		150			0.75	V
r _F	Forward slop resistance					0.55	mΩ
V _{FM}	Peak forward voltage	I _M =750A	25			1.1	V
R _{th(j-c)}	Thermal resistance Junction to heatsink	At 180° sine Single side cooled				0.130	°C /W
V _{iso}	Isolation voltage	50Hz, RM. S, t=1min, i _{iso} : 1mA (max)		2500			V
F _m	Terminal connection torque(M6)				3.0		N.m
	Mounting torque(M8)				4.5		N.m
T _{stg}	Stored temperature			-40		125	°C
W _t	Weight				900		g
Outline							

OUTLINE DRAWING & CIRCUIT DIAGRAM

MD



Rating and Characteristic



Outside Dimension

