



浙江芯芯电子有限公司  
ZHEJIANG XINXIN ELECTIRICAL CO., LTD.

# 产品规格书

## Specification of Products

产品名称：超快恢复二极管

产品型号：MFK200U4

浙江芯芯电子有限公司

ZHEJIANG XINXIN ELECTIRICAL CO., LTD.

地址：浙江省缙云县壶镇镇浙江丽缙五金科技产业园苍山区块内

电话：13857067071

邮编：321404

E-mail:247145749@qq.com

<http://www.zjxxdz1.com>

|     |     |     |
|-----|-----|-----|
| 拟制  | 审核  | 核准  |
| 丁国盛 | 李园利 | 麻伟阳 |

版本号：04    更新日期：2022.6.28



## Ultra-Fast Soft Recovery Diode Module

MFK200U4

### Description

Ultra-FRD module devices are optimized to reduce losses and EMI/RFI in high frequency power conditioning electrical systems. These diode modules are ideally suited for power converters, motors drives and other applications where switching losses are significant portion of the total losses.

### Features


- Repetitive Reverse Voltage :  $V_{RRM} = 400V$
- Low Forward Voltage Drop :  $V_F(\text{typ.}) = 1.2V$
- Average Forward Current :  $I_F(\text{AV.}) = 200A$  @  $T_c = 100^\circ C$
- Ultra-Fast Reverse Recovery Time :  $t_{rr}(\text{typ.}) = 60ns$
- Extensive Characterization of Recovery Parameters
- Reduced EMI and RFI
- Non Isolation Type Package

### Applications

Motor Drives, Free wheel use, High Power Converters, Welders, Various Switching and Telecommunication Power Supply.

### Equivalent Circuit and Package

Equivalent Circuit



Package



Please see the package Out line information

### Absolute Maximum Ratings @ $T_J = 25^\circ C$ (Per Leg)

| Symbol           | Parameter                                                                | Conditions                                                               | Ratings            | Unit       |
|------------------|--------------------------------------------------------------------------|--------------------------------------------------------------------------|--------------------|------------|
| $V_{RRM}$        | Repetitive Peak Reverse Voltage                                          |                                                                          | 400                | V          |
| $V_R(\text{DC})$ | Reverse DC Voltage                                                       |                                                                          | 320                | V          |
| $I_F(\text{AV})$ | Average Forward Current<br>@ $T_c = 25^\circ C$<br>@ $T_c = 100^\circ C$ | Resistive Load                                                           | 400<br>200         | A<br>A     |
| $I_{FSM}$        | Surge (non-repetitive) Forward Current                                   | One Half Cycle at 60Hz,<br>Peak Value                                    | 6000               | A          |
| $I^2_t$          | $I^2t$ for Fusing                                                        | Value for One Cycle Current,<br>$t_w = 8.3ms$ , $T_J = 25^\circ C$ Start | $66.7 \times 10^3$ | $A^2s$     |
| $T_J$            | Junction Temperature                                                     |                                                                          | $-40 \sim 125$     | $^\circ C$ |
| $T_{stg}$        | Storage Temperature                                                      |                                                                          | $-40 \sim 125$     | $^\circ C$ |
| $P_d$            | Maximum Power Dissipation                                                |                                                                          | 870                | W          |
| —                | Mounting Torque                                                          |                                                                          | 4.0                | N.m        |
| —                | Terminal Torque                                                          |                                                                          | 3.0                | N.m        |



### Thermal Characteristics

| Symbol        | Parameter          | Conditions       | Values |      |      | Unit |
|---------------|--------------------|------------------|--------|------|------|------|
|               |                    |                  | Min.   | Typ. | Max. |      |
| $R_{th(j-c)}$ | Thermal Resistance | Junction to Case | -      | -    | 0.12 | °C/W |

### Electrical Characteristics@ $T_J=25^{\circ}\text{C}$ (unless otherwise specified)

| Symbol    | Parameter                       | Conditions                                                                            |                             | Values |      |      | Unit |
|-----------|---------------------------------|---------------------------------------------------------------------------------------|-----------------------------|--------|------|------|------|
|           |                                 |                                                                                       |                             | Min.   | Typ. | Max. |      |
| $V_R$     | Cathode Anode Breakdown Voltage | $I_R = 100\mu\text{A}$                                                                |                             | 400    | -    | -    | V    |
| $V_{FM}$  | Maximum Forward Voltage         | $I_{FM} = 450\text{A}$ , $T_c = 25^{\circ}\text{C}$                                   |                             | -      | 1.2  | 1.3  | V    |
|           |                                 | $I_{FM} = 450\text{A}$ , $T_c = 100^{\circ}\text{C}$                                  |                             | -      | 0.8  | 1.2  | V    |
| $I_{RRM}$ | Repetitive Peak Reverse Current | $T_c = 100^{\circ}\text{C}$ , $V_{RRM}$ applied                                       |                             | -      | -    | 10.0 | mA   |
| $t_{rr}$  | Reverse Recovery Time           | $I_{FM} = 200\text{A}$ ,<br>$V_R = 300\text{V}$<br>$di/dt = -100\text{A}/\mu\text{s}$ | $T_c = 25^{\circ}\text{C}$  | -      | 60   | 70   | ns   |
|           |                                 |                                                                                       | $T_c = 100^{\circ}\text{C}$ | -      | 100  | -    | ns   |

### Performance Curves




Fig. 1 : Typical Forward Voltage Drop  
vs. Instantaneous Forward Current




Fig. 2 : Typical Reverse Recovery Time  
vs.  $-di/dt$




Fig. 3 : Transient Thermal Impedance ( $Z_{thjc}$ )  
Characteristics




Fig. 4 : Forward Current Derating Curve

# Outside Dimension

