



浙江芯芯电子有限公司
ZHEJIANG XINXIN ELECTIRICAL CO., LTD.

产品规格书

Specification of Products

产品名称：可控硅模块

产品型号：MTC350A

浙江芯芯电子有限公司

ZHEJIANG XINXIN ELECTIRICAL CO., LTD.

地址：浙江省缙云县壶镇镇浙江丽缙五金科技产业园苍山区块内

电话：13857067071

邮编：321404

E-mail:247145749@qq.com


<http://www.zjxxdz1.com>

拟制	审核	核准
丁国盛	李园利	麻伟阳

版本号：04 更新日期：2022.6.28

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T _j (°C)	VALUE			UNIT
				Min	Type	Max	
I _{T(AV)}	Mean on-state current	180° half sinewave 50Hz Single side cooled, T _j =85°C	125			350	A
I _{T(RMS)}	RMS on-state current	Single side cooled, T _j =85°C	125			550	A
V _{DRM} V _{RRM}	Repetitive peak off-state voltage Repetitive peak reverse voltage	V _{DRM} &V _{RRM} tp=10ms V _{DSM} &V _{RSM} = V _{DRM} &V _{RRM} +200V respectively	125	600		1800	V
I _{DRM} I _{RRM}	Repetitive peak current	at V _{DRM} at V _{RRM}	125			40	mA
I _{TSM}	Surge on-state current	10ms half sinewave	125			11.0	KA
I ² t	I ² T for fusing coordination	V _R =60%V _{RRM}				617	A ² s*10 ³
V _{TO}	Threshold voltage		125			0.80	V
r _T	On-state slop resistance					0.50	mΩ
V _{TM}	Peak on-state voltage	T _M =1050A	125			1.5	V
dv/dt	Critical rate of rise of off-state voltage	V _{DM} =67%V _{DRM}	125			800	V/μs
di/dt	Critical rate of rise of on-state current	From 67%V _{DRM} to 1050A, Gate source 1.5A t _r ≤0.5μs Repetitive	125			150	A/μs
I _{GT}	Gate trigger current	V _A =12V, I _A =1A	25	30		180	mA
V _{GT}	Gate trigger voltage			1.0		2.5	V
I _H	Holding current			20		100	mA
V _{GD}	Non-trigger gate voltage	At 67%V _{DRM}	125			0.2	V
R _{th(j-c)}	Thermal resistance Junction to heatsink	At 180° sine Single side cooled				0.090	°C /W
V _{iso}	Isolation voltage	50Hz, R.M. S, t=1min, i _{so} : 1mA MAX)		2500			V
F _m	Thermal connection torque(M10)				6.0		N.m
	Mounting torque(M6)				3.0		N.m
T _{stg}	Stored temperature			-40		140	°C
W _t	Weight				1575		g
Outline							

OUTLINE DRAWING & CIRCUIT DIAGRAM



Rating and Characteristic




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

Rating and Characteristic




Fig. 7




Fig. 8




Fig. 9




Fig. 10

Technical drawing of the K222K terminal block, showing front and side views with dimensions in millimeters.

Front View Dimensions:

- Overall width: 125 mm
- Overall height: 63 mm
- Terminal pitch (center-to-center): 38 mm
- Distance from left edge to first terminal center: 12 mm
- Distance between terminal centers: 42 mm
- Terminal diameter: $4-\phi 6.5$
- Distance from bottom edge to terminal center line: 93 mm
- Distance from bottom edge to terminal center line (including mounting holes): 108 mm
- Mounting hole diameter: $\phi 6.5$
- Mounting hole spacing: 48 mm
- Mounting hole diameter: $\phi 6.5$

Side View Dimensions:

- Overall height: 64 mm
- Distance from bottom edge to top of terminal block: 30.5 mm
- Distance from bottom edge to top of terminal block (including mounting holes): 47 mm
- Distance from bottom edge to top of terminal block (including mounting holes): 52 mm
- Distance from bottom edge to top of terminal block (including mounting holes): 57 mm
- Distance from bottom edge to top of terminal block (including mounting holes): 69 mm

