



浙江芯芯电子有限公司
ZHEJIANG XINXIN ELECTIRICAL CO., LTD.

产品规格书

Specification of Products

产品名称：螺栓型

产品型号：ZP70A

浙江芯芯电子有限公司

ZHEJIANG XINXIN ELECTIRICAL CO., LTD.

地址：浙江省缙云县壶镇镇浙江丽缙五金科技产业园苍山区块内

电话：13857067071

邮编：321404

E-mail:247145749@qq.com

<http://www.zjxxdz1.com>

拟制	审核	核准
丁国盛	李园利	麻伟阳

版本号：04 更新日期：2022.6.28

SY M BOL	CH ARACTERIS TIC	TES T CONDI TIONS	T _j (°C)	VALUE			UNIT
				M in	Type	M ax	
I _{F(AV)}	M ean foward current	180° half sinwave 50Hz single side cooled _h T=55° C	150			110	A
I _{F(AV)}	M ean foward current	180° half sineave 50Hz single side cooled _h T=90° C	150			70	A
V _{RRM}	Repetitivepeak reverse voltage	V _{RRM} tp=10ms V _{RSM} = V _{RRM} +100V	150	100		2000	V
I _{RRM}	Repetitivepeak current	at V _{RRM}	150			10	mA
I _{FSM}	Surge foward current	10ms half sineave	150			1.64	KA
I ² T I	² T for fusing coordination	V _R =0.6V _{RRM}				13.5	A ² s*10 ³
V _{FO}	Threshold voltage		150			1.65	V
r _F	Forward slop resistance					1.42	mW
V _{FM}	Peak on-state voltage	T _M =300A	150			2.0	V
I _{rm}	Reverse recovery current	I _M =300A, tp=1000 μs, di/dt=-20A/μs, V _R =50V	150			30	A
t _{rr}	Reverse recovery time					4	μs
Q _{rr}	Recovery charge					60	μC
R _{th(j-h)}	Thermal resistance Junction to heatsink	At 180° sine single side cooled Clamping torque 17 Nm				0.22	°C /W
F _m	M ounting torque			13		19	N.m
T _{stg}	Stored temperature			-40		160	° C
Outline							

Outline



